

HD-A137 727

COMPONENT RELEVANCY IN MULTISTATE SYSTEMS(U) FLORIDA  
STATE UNIV TALLAHASSEE DEPT OF STATISTICS  
E EL-NEWELHI ET AL SEP 83 FSU-STATISTICS-M670

1/1


UNCLASSIFIED

AFOSR-TR-84-0048 F49620-82-K-0007

F/G 12/1

NL





MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

AFOSR-TR. 84-0048

(4)

ADA-137 727

by

Emad El-Newehi<sup>1</sup> and Frank Proschan<sup>2</sup>  
University of Illinois at Chicago  
and  
Florida State University

DTIC  
ELECTE  
FEB 13 1984  
B

DTIC FILE COPY

**DISTRIBUTION STATEMENT A**

Approved for public release;  
Distribution Unlimited

Approved for public release;  
distribution unlimited.

84 02 10 092

# REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION <b>UNCLASSIFIED</b>		1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited.	
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE		5. MONITORING ORGANIZATION REPORT NUMBER(S) <b>AFOSR-TR. 84-0048</b>	
4. PERFORMING ORGANIZATION REPORT NUMBER(S) FSU M670		7a. NAME OF MONITORING ORGANIZATION Air Force Office of Scientific Research	
6a. NAME OF PERFORMING ORGANIZATION Florida State University	6b. OFFICE SYMBOL (If applicable)	7b. ADDRESS (City, State and ZIP Code) Directorate of Mathematical & Information Sciences, Bolling AFB DC 20332	
6c. ADDRESS (City, State and ZIP Code) Dept. of Statistics Tallahassee, Fla. 32306	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER F49620-82-K-0007		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION AFOSR	8b. OFFICE SYMBOL (If applicable) NM	10. SOURCE OF FUNDING NOS.	
8c. ADDRESS (City, State and ZIP Code) Bolling AFB DC 20332		PROGRAM ELEMENT NO. 61102F	PROJECT NO. 2304
11. TITLE (Include Security Classification) COMPONENT RELEVANCY IN MULTISTATE SYSTEMS		TASK NO. A5	WORK UNIT NO.
12. PERSONAL AUTHOR(S) Emad El-Neweihi and Frank Proschan*			
13a. TYPE OF REPORT Technical	13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Yr., Mo., Day) SEP 83	15. PAGE COUNT 11
16. SUPPLEMENTARY NOTATION Frank Proschan is with the Department of Statistics, Florida State University, Tallahassee FL 32306.			
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB. GR.	
		Multistate systems, relevant components, redundancy, structural importance, coherent structures, performance levels, reliability.	
19. ABSTRACT (Continue on reverse if necessary and identify by block number) The authors define a hierarchy of six successively weaker conditions for component relevance in a multistate of M+1 performance levels. The authors show that the six conditions are distinct except for M=1,2. The authors present basic structural properties corresponding to the six conditions: (1) the definition and properties of the dual structure, (2) redundancy at a lower level is preferable to redundancy at a higher level, and (3) the definition and properties of the structural importance of components.			
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT UNCLASSIFIED/UNLIMITED <input checked="" type="checkbox"/> SAME AS RPT. <input checked="" type="checkbox"/> DTIC USERS <input type="checkbox"/>		21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED	

Component Relevancy in Multistate Systems

by

Emad El-Neweihi<sup>1</sup> and Frank Proschan<sup>2</sup>  
University of Illinois at Chicago  
and  
Florida State University

September, 1983

**DTIC**  
**ELECTE**  
**FEB 13 1984**  
**S D**  
**B**

University of Illinois at Chicago  
Department of Mathematics, Statistics, and Computer  
Science  
P.O. Box 4348, Chicago, Illinois 60680

<sup>1</sup>Research sponsored by the Air Force Office of Scientific Research, AFSC, USAF, under Grant AFOSR-80-0170.

<sup>2</sup>Research sponsored by the Air Force Office of Scientific Research, Air Force Systems Command, USAF, under Grant Number ~~AFOSR-82-K-0007~~. The <sup>249620-82-K-0007</sup> U.S. Government is authorized to reproduce and distribute reprints for Governmental purposes notwithstanding any copyright notation thereon.

Key words: Multistate systems, relevant components, redundancy, structural importance, coherent structures, performance levels, reliability

AMS Subject Classification: 60K10

**DISTRIBUTION STATEMENT A**  
**Approved for public release;**  
**Distribution Unlimited**

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH (AFSC)  
NOTICE OF TRANSMISSION TO DTIC  
This technical report has been reviewed and is approved for release IAW AFM 10-1.3.  
Distribution is unlimited.  
MATTHEW J. KERPER  
Chief, Technical Information Division

# Component Relevancy in Multistate Systems

by

Emad El-Neweihi and Frank Proschan

## Abstract

*The authors*  
We define a hierarchy of six successively weaker conditions for component relevancy in a multistate structure of  $M+1$  performance levels. We show that the six conditions are distinct except for  $M=1,2$ . *Proschan see* We present basic structural properties corresponding to the six conditions: (a) the definition and properties of the dual structure, (b) redundancy at a lower level is preferable to redundancy at a higher level, and (c) the definition and properties of the structural importance of components.

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



## 0. Introduction and Summary.

In defining a binary coherent system, a key requirement is that each component be relevant to system functioning or failure. This requirement avoids the possibility of components that play no role in system functioning or failure. Only one natural definition of relevancy is possible.

In the multistate model, where each component may be in any of states  $0, 1, \dots, M > 1$ , a variety of alternative relevancy requirements are possible. In this paper we list six reasonable relevancy requirements, forming a hierarchy of increasingly weaker requirements.

In Section 1, we present notation and terminology. Section 2 lists the six relevancy conditions ranging from the strongest to the weakest. We show that the six conditions are distinct except for the cases  $M = 1, 2$ . Finally, in Section 3, we present basic structural properties corresponding to the six relevancy conditions. Thus, we define and study the dual structure, obtain the well known design principle that redundancy at a lower level is preferable to redundancy at a higher level, and define and study the structural importance of components.

## 1. Notation and Terminology.

The vector  $\underline{x} = (x_1, \dots, x_n)$  denotes the vector of states of components  $1, \dots, n$ .

$C = \{1, \dots, n\}$  denotes the set of component indices.

$(j_i, \underline{x}) \equiv (x_1, \dots, x_{i-1}, j, x_{i+1}, \dots, x_n)$ , where  $j = 0, 1, \dots, M$ .

$(\cdot_i, \underline{x}) \equiv (x_1, \dots, x_{i-1}, \cdot, x_{i+1}, \dots, x_n)$ .

$\underline{j} \equiv (j, \dots, j)$ , where  $j = 0, 1, \dots, M$ .

$$x \vee y \equiv \max(x, y).$$

$$\underline{x} \vee \underline{y} \equiv (x_1 \vee y_1, \dots, x_n \vee y_n).$$

$$x \wedge y \equiv \min(x, y).$$

$$\underline{x} \wedge \underline{y} \equiv (x_1 \wedge y_1, \dots, x_n \wedge y_n).$$

When we say  $\phi(x_1, \dots, x_n)$  is nondecreasing we mean  $\phi$  is nondecreasing in each argument.

Given a set  $S$ ,  $S^n$  denotes its  $n$ <sup>th</sup> Cartesian power.

## 2. Levels of Component Relevancy.

A basic ingredient in the theory of binary coherent systems is the structure function  $\phi: \{0,1\}^n \rightarrow \{0,1\}$  which determines the state of the system in terms of the states of the  $n$  components. The following two conditions are required for a binary system to be a coherent structure [1, Def. 2.1, p.6]:

- (i) The function  $\phi(\underline{x})$  is nondecreasing.
- (ii) For each  $i$  there exists a vector  $(\cdot_i, \underline{x})$  such that  $\phi(1_i, \underline{x}) > \phi(0_i, \underline{x})$ .

Condition (i) expresses the reasonable assumption that improving component performance should not degrade system performance. Condition (ii) asserts that each component is relevant to system performance, thus eliminating from consideration components that have no effect on system performance. It follows from (i) and (ii) that

$$(iii) \quad \phi(\underline{1}) = 1 \quad \text{and} \quad \phi(\underline{0}) = 0.$$

Recently researchers felt the need to develop the theory of multistate coherent systems to describe more adequately the performance of components and systems which have more than two levels of performance. Again a basic



ingredient in such a theory is the structure function  $\phi: S^n \rightarrow S$ , where  $S = \{0, 1, \dots, M\}$  is the set representing levels of performance varying from perfect functioning  $M$  to total failure  $0$ . (We concentrate in this paper on the case where  $S$  is finite.) One possible approach to extend the concept of binary coherent structures is to impose on  $\phi$  a set of "reasonable" conditions which generalize conditions (i) and (ii). Condition (i) is extended in a straightforward manner by requiring  $\phi$  to be non-decreasing. It turns out, however, that the relevancy condition can be extended in many different ways, each leading to a distinct class of multi-state "coherent" structures. In a multistate model, relevancy becomes a more complex concept that admits different mathematical formulations. The following are successively weaker versions of relevancy:

(ii)' For every component  $i$ , there exists a vector  $(\cdot_i, \underline{x})$  such that  $\phi(j_i, \underline{x}) = j$ ,  $j = 0, 1, \dots, M$ .

(ii)'' For every component  $i$  and level  $j$ , there exists a vector  $(\cdot_i, \underline{x})$  such that  $\phi(j_i, \underline{x}) = j$  while  $\phi(l_i, \underline{x}) \neq j$  for  $l \neq j$ .

(ii)''' For every component  $i$  and level  $j \geq 1$ , there exists a vector  $(\cdot_i, \underline{x})$  such that  $\phi(j_i, \underline{x}) \geq j$  and  $\phi((j-1)_i, \underline{x}) \leq j-1$ .

(ii)(iv) For every component  $i$  and level  $j \geq 1$ , there exists a vector  $(\cdot_i, \underline{x})$  such that  $\phi((j-1)_i, \underline{x}) < \phi(j_i, \underline{x})$ .

(ii)(v) For every component  $i$  and level  $j \geq 1$ , there exists a vector  $(\cdot_i, \underline{x})$  such that  $\phi(0_i, \underline{x}) < \phi(j_i, \underline{x})$ .

(ii)(vi) For every component  $i$ , there exists a vector  $(\cdot_i, \underline{x})$  such that  $\phi(0_i, \underline{x}) < \phi(M_i, \underline{x})$ .

Among the six conditions above, the first five indicate a degree of relevancy of each component to every level of performance, while the last merely states that every component is relevant to the system. Condition

(ii)'' is due to El-Neweihi, Proschan, and Sethuraman (1978), Condition (ii)''' is due to Natvig (1982), Conditions (ii)<sup>(iv)</sup>, (ii)<sup>(v)</sup> are due to Griffith (1980), and the remaining conditions are new. It should also be remarked that the condition

$$(iii)' \quad \phi(j) = j, \quad j = 0, 1, \dots, M,$$

which generalizes Condition (iii) is not necessarily satisfied by a non-decreasing structure function  $\phi$  which satisfies one of the relevancy axioms (except, of course, when  $M = 1$ ).

When  $M = 1$  all the above relevancy conditions are equivalent; also when  $M = 2$  Conditions (ii)' and (ii)'' are equivalent. The following examples show that in general the above relevancy axioms are not equivalent.

**Example 2.1.** Let  $n = 2, M = 3$ . Define  $\phi$  by  $\phi(0,0) = 0, \phi(1,0) = \phi(0,1) = \phi(1,1) = 1, \phi(0,2) = \phi(0,3) = \phi(1,2) = \phi(2,0) = \phi(2,1) = \phi(2,2) = \phi(3,0) = 2, \phi(1,3) = \phi(2,3) = \phi(3,1) = \phi(3,2) = \phi(3,3) = 3$ . Then  $\phi$  satisfies Condition (ii)'' but  $\phi$  does not satisfy Condition (ii)'.

**Example 2.2.** Let  $n = 2, M = 2$ . Define  $\phi$  by  $\phi(0,0) = 0, \phi(0,1) = \phi(0,2) = \phi(1,0) = \phi(1,1) = \phi(1,2) = \phi(2,0) = \phi(2,1) = 1, \phi(2,2) = 2$ . Then  $\phi$  satisfies Condition (ii)''' but  $\phi$  does not satisfy Condition (ii)'.

**Example 2.3.** Let  $n = 2, M = 2$ . Define  $\phi$  by  $\phi(0,0) = \phi(1,0) = \phi(0,1) = 0, \phi(1,1) = \phi(2,1) = \phi(2,0) = \phi(0,2) = 1, \phi(1,2) = \phi(2,2) = 2$ . Then  $\phi$  satisfies Condition (ii)<sup>(iv)</sup> but does not satisfy Condition (ii)'''.

**Example 2.4.** Let  $n = 2, M = 2$ . Define  $\phi$  by  $\phi(0,0) = 0, \phi(0,1) = \phi(1,0) = \phi(1,1) = \phi(2,0) = \phi(2,1) = 1, \phi(0,2) = \phi(1,2) = \phi(2,2) = 2$ . Then  $\phi$  satisfies Condition (ii)<sup>(v)</sup> but  $\phi$  does not satisfy Condition (ii)<sup>(iv)</sup>.

Example 2.5. Let  $n = 2$ ,  $M = 2$ . Define  $\phi$  by  $\phi(0,0) = \phi(1,0) = 0$ ,  $\phi(0,1) = \phi(0,2) = \phi(1,1) = \phi(1,2) = \phi(2,0) = \phi(2,1) = 1$ ,  $\phi(2,2) = 2$ . Then  $\phi$  satisfies Condition (ii)<sup>(vi)</sup> but does not satisfy Condition (ii)<sup>(v)</sup>.

A class of nondecreasing structure functions which satisfy (iii)' and one of the relevancy axioms may be designated as a class of multistate coherent systems. In the following section we examine some interesting properties and concepts for such classes which are closely related to the relevancy axioms.

### 3. Structural Properties Related To Relevancy.

As in the binary case, a dual structure for each multistate structure can be defined:

Definition 3.1. Let  $\phi$  be the structure function of a multistate system. The dual structure function  $\phi^D$  is given by:

$$\phi^D(\underline{x}) = M - \phi(M - \underline{x}).$$

The following interesting question naturally arises: Do the components of the dual structure  $\phi^D$  inherit the relevancy property enjoyed by the components of  $\phi$ ? The following theorem asserts that with the exception of Condition (ii)<sup>(v)</sup>, the answer is yes.

Theorem 3.2. Let  $\phi$  be a multistate structure function which satisfies one of the Conditions (ii)' through (ii)<sup>(iv)</sup> or Condition (ii)<sup>(vi)</sup>. Then the dual structure function  $\phi^D$  satisfies the same condition.

Proof. The proof is straightforward and is therefore omitted.

Example 3.3. Let  $\phi$  be defined as in Example 2.4. Then  $\phi$  satisfies Condition (ii)<sup>(v)</sup> but  $\phi^D$  does not satisfy the same condition.

Design engineers have used the well known principle that redundancy at the component level is preferable to redundancy at the system level. This principle still holds in the multistate model and is translated into mathematical form in (a) of the following theorem; (b) is a dual result.

Theorem 3.4. Let  $\phi$  be a nondecreasing multistate structure function.

Then

$$(a) \quad \phi(\underline{x} \vee \underline{y}) \geq \phi(\underline{x}) \vee \phi(\underline{y}) \quad \text{for all } \underline{x} \text{ and } \underline{y}.$$

$$(b) \quad \phi(\underline{x} \wedge \underline{y}) \leq \phi(\underline{x}) \wedge \phi(\underline{y}) \quad \text{for all } \underline{x} \text{ and } \underline{y}.$$

The above theorem is an immediate consequence of the monotonicity of  $\phi$ . The following less trivial result is due to El-Newehi, Proschan, and Sethuraman (1978):

Let the nondecreasing structure function  $\phi$  also satisfy Condition (ii)''. Then equality holds in (a) ((b)) for all  $\underline{x}$  and  $\underline{y}$  implies that the system is parallel (series).

An extension to the above result is achieved by Griffith (1980) by replacing (ii)'' with the weaker Condition (ii)<sup>(iv)</sup>. However, Griffith (1980) showed by an example that the same result is not true if (ii)'' is replaced by (ii)<sup>(vi)</sup>. The following example shows that Condition (ii)<sup>(v)</sup> is not sufficiently strong.

Example 3.5. Let  $n = 2$ ,  $M = 2$ . Let  $\phi$  be as defined in Example 2.4. Then  $\phi$  satisfies Condition (ii)<sup>(v)</sup>,  $\phi(\underline{x} \vee \underline{y}) = \phi(\underline{x}) \vee \phi(\underline{y})$  for all  $\underline{x}$  and  $\underline{y}$  but  $\phi(\underline{x}) \neq \max_{1 \leq i \leq n} x_i$

A measure of the structural importance of each component to a given system is of obvious practical significance. In the binary case the importance of component  $i$  to a coherent structure  $\phi$  is given by

$I(i) = \frac{1}{2^{n-1}} \text{Card}\{(\cdot_i, \underline{x}) : \phi(0_i, \underline{x}) < \phi(1_i, \underline{x})\}$ . Note that the relevancy Condition (ii) guarantees that  $I(i) > 0$  for each  $i = 1, \dots, n$ .

Generalizations of such a measure in the multistate setting are now evident.

Let  $\phi$  be a nondecreasing multistate structure. A measure of the importance of component  $i$  to the structure  $\phi$  can be given by

$I'(i) = \frac{1}{(M+1)^{n-1}} \text{Card}\{(\cdot_i, \underline{x}) : \phi(j_i, \underline{x}) = j, j = 0, 1, \dots, M\}$ . Note that  $I'(i) > 0$  for each  $i$  if and only if  $\phi$  satisfies Condition (ii)'.  
 measures  $I''(i)$ ,  $I'''(i)$ ,  $I^{(iv)}(i)$ ,  $I^{(v)}(i)$ , and  $I^{(vi)}(i)$  are similarly defined. Note that  $I'(i) \leq I''(i) \leq I'''(i) \leq I^{(iv)}(i) \leq I^{(v)}(i) \leq I^{(vi)}(i)$ .  
 Also observe that each of those six measures of structural importance has its natural probabilistic counterpart (see Block and Savits (1982)).

Finally, we shed some light on preservation of the various relevancy axioms under modular decomposition. A question raised and answered by Griffith (1980) is whether a "relevant" component within a "relevant" module is "relevant" in the system. The answer is yes if relevancy is defined in terms of Conditions (ii)'' and (ii)<sup>(iv)</sup>. However, an example is given by Griffith (1980) to show that this is not necessarily the case for Condition (ii)<sup>(vi)</sup>. It can be easily shown that the answer is still yes if relevancy is defined in terms of Conditions (ii)' and (ii)'''. The following example shows that this is not necessarily the case for Condition (ii)<sup>(v)</sup>.

**Example 3.6.** Let  $n = 2, M = 2$ . Define  $\phi$  by  $\phi(0,0) = \phi(1,0) = \phi(2,0) = 0$ ,  $\phi(0,1) = \phi(1,1) = \phi(2,1) = \phi(0,2) = 1$ ,  $\phi(1,2) = \phi(2,2) = 2$ . Now let  $\psi(x_1, x_2, x_3) = \phi(\phi(x_1, x_2), x_3)$ .

REFERENCES

- [1] Barlow, R. E. and Proschan, F. (1981). Statistical Theory of Reliability and Life Testing. To Begin With, Silver Spring, Maryland.
- [2] Block, H. W. and Savits, T. H. (1982). A decomposition for multistate monotone systems. J. Appl. Prob., 19, 391-402.
- [3] El-Newehi, E., Proschan, F., and Sethuraman, J. (1978). Multistate coherent systems. J. Appl. Prob., 15, 675-688.
- [4] Griffith, W. S. (1980). Multistate reliability models. J. Appl. Prob., 17, 735-744.
- [5] Natvig, B. (1982). Two suggestions of how to define a multistate coherent system. Adv. Appl. Prob., 14, 434-455.

END

FILMED

3-84

DTIC